

Manual Valve

PRODUCT CATALOGUE



Flanged Ball Valve

Specifications

[Size Range] DN50-DN450
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Flange Standard] GB/ANSI/JIS/DIN



Integrated Leak-proof Ball Valve

Specifications

[Size Range] DN50-DN450
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Flange Standard] GB/ANSI/JIS/DIN



Wafer Type Flanged Ball Valve

Specifications

[Size Range] DN50-DN450
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Flange Standard] GB/ANSI/JIS/DIN





3PC Ball Valve With Flange

Specifications

[Size Range] DN50-DN450
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Flange Standard] GB/ANSI/JIS/DIN



3-Way Ball Valve

Specifications

[Size Range] DN50-DN800
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-200Bar
[Operating Temperature] 425°C
[Flange Standard] GB/ANSI/JIS/DIN



Baiting Valve

Specifications

[Size Range] DN50-DN600
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Flange Standard] GB/ANSI/JIS/DIN





Two-Piece Threaded Ball Valve

Specifications

[Size Range] DN15-DN150
[Body Material] WCB,SS304,SS316,Brass
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Thread Standard] BSPP/G/NPT



High pressure Valve series

Specifications

[Size Range] DN15-DN350
[Body Material] WCB,SS304,SS316,Brass
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Thread Standard] BSPP/G/NPT



1-Piece Threaded Ball Valve

Specifications

[Size Range] DN15-DN200[Body Material] WCB,SS304,SS316,Brass[Operating Pressure] 10-100Bar[Operating Temperature] 425°C[Thread Standard] BSPP/G/NPT





3-Piece Threaded Ball Valve

Specifications

[Size Range] DN15-DN150[Body Material] WCB,SS304,SS316,Brass[Operating Pressure] 10-100Bar[Operating Temperature] 425°C[Thread Standard] BSPP/G/NPT



3-Piece Welded Ball Valve

Specifications

[Size Range] DN15-DN150[Body Material] WCB,SS304,SS316,Brass[Operating Pressure] 10-100Bar[Operating Temperature] 425°C[Thread Standard] BSPP/G/NPT



3-Piece Quick-Connect Ball Valve

Specifications

[Size Range] DN30-DN500
[Body Material] WCB,SS304,SS316,Brass
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Connection End] Tri Clamp





Internal Threaded 3-Way Ball Valve

Specifications

[Size Range] DN15-DN150
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Thread Standard] BSPP/G/NPT



External Threaded Ball Valve

Specifications

[Size Range] DN15-DN250
[Body Material] WCB,SS304,SS316,Brass
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Thread Standard] BSPP/G/NPT



Internal Threaded Ball Valve

Specifications

[Size Range] DN15-DN400
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Thread Standard] BSPP/G/NPT





Y-Type Internal Threaded Strainer

Specifications

[Size Range] DN15-DN150
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Thread Standard] BSPP/G/NPT



Stainless Steel Internal Threaded Gate Valve

Specifications

[Size Range] DN15-DN150[Body Material] WCB,SS304,SS316,Brass[Operating Pressure] 10-100Bar[Operating Temperature] 425°C[Thread Standard] BSPP/G/NPT



American Style Internal Threaded Globe Valve

Specifications

[Size Range] DN15-DN200
[Body Material] WCB,SS304,SS316,Brass
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Thread Standard] BSPP/G/NPT





Internal Threaded Check Valve

Specifications

[Size Range] DN15-DN150
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Thread Standard] BSPP/G/NPT



Clamp-Type Check Valve

Specifications

[Size Range] DN100-DN1200
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Flange Standard] GB/ANSI/JIS/DIN



Globe Valve

Specifications

[Size Range] DN15-DN300
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Flange Standard] GB/ANSI/JIS/DIN





Gate Valve

Specifications

[Size Range] DN20-DN350
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Flange Standard] GB/ANSI/JIS/DIN



Check Valve

Specifications

[Size Range] DN20-DN600
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Flange Standard] GB/ANSI/JIS/DIN



Y-Type Flanged Strainer

Specifications

[Size Range] DN30-DN400
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Flange Standard] GB/ANSI/JIS/DIN





Forged Steel Globe Valve

Specifications

[Size Range] DN15-DN500
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Flange Standard] GB/ANSI/JIS/DIN



Forged Steel Gate Valve

Specifications

[Size Range] DN15-DN450
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Flange Standard] GB/ANSI/JIS/DIN



Forged Steel Check Valve

Specifications

[Size Range] DN10-DN200
[Body Material] WCB,SS304,SS316
[Operating Pressure] 10-100Bar
[Operating Temperature] 425°C
[Flange Standard] GB/ANSI/JIS/DIN

